

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-7. (Canceled)

8. (New) A fuel injection device for internal combustion engines, comprising,

a control chamber (2),

a control valve (6) having first, second and third valve positions, the control valve (6) being located between a high-pressure side (5) and a low-pressure side (7) and being operable to open or block the communication of the control chamber (2) with the low-pressure side (7),

an outlet throttle (8) located between the control valve (6) and the low-pressure side (7), and

means (13) moving the control valve (6) between its first, second and third positions

the control valve (6) blocking the communication of the control chamber (2) with the low-pressure side (7) in its first position, the control chamber (2) communicating with the low-pressure side (7) via a first outlet conduit (14) when the control valve (6) is in its second position, and the control chamber (2) communicating with the low-pressure side (7) via a second outlet conduit (16) having an outlet throttle (15) when the control valve (6) is in its third position.

9. **(New)** The fuel injection device of claim 8, wherein the outlet throttle (15) of the second outlet conduit (16) has a higher throttle resistance than the outlet throttle (8) on the low-pressure side.

10. **(New)** The fuel injection device of claim 8, wherein in the second valve position, the control chamber (2) communicates with the low-pressure side (7) via the second outlet conduit (16) as well.

11. **(New)** The fuel injection device of claim 9, wherein in the second valve position, the control chamber (2) communicates with the low-pressure side (7) via the second outlet conduit (16) as well.

12. **(New)** The fuel injection device of claim 8, wherein the control valve (6) is embodied as a double seat valve, with a valve body (9) that is axially adjustable in a valve chamber (10) between two valve seats (11, 12), and one valve seat (11) communicates with the first outlet conduit (14), the other valve seat (12) communicates with the low-pressure side (7), and the valve chamber (10) communicates with the second outlet conduit (16).

13. **(New)** The fuel injection device of claim 9, wherein the control valve (6) is embodied as a double seat valve, with a valve body (9) that is axially adjustable in a valve chamber (10) between two valve seats (11, 12), and one valve seat (11) communicates with the first outlet conduit (14), the other valve seat (12) communicates with the low-pressure side (7), and the valve chamber (10) communicates with the second outlet conduit (16).

14. (New) The fuel injection device of claim 10, wherein the control valve (6) is embodied as a double seat valve, with a valve body (9) that is axially adjustable in a valve chamber (10) between two valve seats (11, 12), and one valve seat (11) communicates with the first outlet conduit (14), the other valve seat (12) communicates with the low-pressure side (7), and the valve chamber (10) communicates with the second outlet conduit (16).

15. (New) The fuel injection device of claim 11, wherein the control valve (6) is embodied as a double seat valve, with a valve body (9) that is axially adjustable in a valve chamber (10) between two valve seats (11, 12), and one valve seat (11) communicates with the first outlet conduit (14), the other valve seat (12) communicates with the low-pressure side (7), and the valve chamber (10) communicates with the second outlet conduit (16).

16. (New) The fuel injection device of claim 8, wherein the control chamber (2) is connected to the high-pressure side (5) via an inlet throttle (4), which has a lesser throttle resistance than the outlet throttle (15) of the second outlet conduit (16).

17. (New) The fuel injection device of claim 9, wherein the control chamber (2) is connected to the high-pressure side (5) via an inlet throttle (4), which has a lesser throttle resistance than the outlet throttle (15) of the second outlet conduit (16).

18. (New) The fuel injection device of claim 10, wherein the control chamber (2) is connected to the high-pressure side (5) via an inlet throttle (4), which has a lesser throttle resistance than the outlet throttle (15) of the second outlet conduit (16).

19. **(New)** The fuel injection device of claim 12, wherein the control chamber (2) is connected to the high-pressure side (5) via an inlet throttle (4), which has a lesser throttle resistance than the outlet throttle (15) of the second outlet conduit (16).
20. **(New)** The fuel injection device of claim 8, wherein the first outlet conduit (14) is connected to the high-pressure side (5) via an inlet throttle (18).
21. **(New)** The fuel injection device of claim 9, wherein the first outlet conduit (14) is connected to the high-pressure side (5) via an inlet throttle (18).
22. **(New)** The fuel injection device of claim 10, wherein the first outlet conduit (14) is connected to the high-pressure side (5) via an inlet throttle (18).
23. **(New)** The fuel injection device of claim 12, wherein the first outlet conduit (14) is connected to the high-pressure side (5) via an inlet throttle (18).
24. **(New)** The fuel injection device of claim 16, wherein the first outlet conduit (14) is connected to the high-pressure side (5) via an inlet throttle (18).
25. **(New)** The fuel injection device of claim 12, wherein the means moving the valve body (9) between the first, second and third valve positions comprises a piezoelectric actuator (13).

26. (New) The fuel injection device of claim 16, wherein the means moving the valve body (9) between the first, second and third valve positions comprises a piezoelectric actuator (13).

27. (New) The fuel injection device of claim 20, wherein the means moving the valve body (9) between the first, second and third valve positions comprises a piezoelectric actuator (13).